

IRIS CYC 1000w - 1250w

Model 53-21 to 53-24



Pole operated version

Single or multiple compartment cyclorama lights in horizontal or vertical arrangement. Luminaire designed for medium-size and larger TV studios. The asymmetrical reflector design provides an exceptionally even distribution over the entire projected area of the cyclorama. Pole Operation version available for the adjustment of tilt angle.

- Iris Cyc model 53-21, Single compartment 1 lamp.
- Iris Cyc model 53-22, Double compartment 2 lamps.
- Iris Cyc model 53-23, Three compartment 3 lamps.
- Iris Cyc model 53-24, Four compartment 4 lamps, in vertical or horizontal arrangement.
- Available Manual and Pole operation (PO) versions.
- Accepts 625W, 1000W or 1250W linear 189mm quartz-halogen 3200K lamps.
- Safety mesh.

PHOTOMETRIC DATA

With lamp FFT 1000w 120v - Hanging at 4 mts. - 45° angle - Distance from Cyclorama 2 meters.



Lateral spacing between two units (centre to centre): 2,4 meters.

IRIS CYC SYSTEM

CODE	53-21	53-22	53-23	53-24
N° of lights	1	2	3	4
N° of circuits	1	2	3	4
Height (mt) T	0.36	0.36	0.36	0.36
Width (mt) S	0.52	0.94	1.36	1.78
Depth (mt) U	0.36	0.36	0.36	0.36

LAMPS

ANSI COD.	LIF COD.	BRAND CODE	W	V	SOCKET	LIFE HS	°K
	P2/10	7775R PHILIPS	625	220	R7-S	150	3200
EKM	P2/7	13989 PHILIPS	1000	220	R7-S	200	3200
	P2/12	6358 PHILIPS	1250	220	R7-S	200	3200
FFT		FFT GE	1000	120	R7-S	400	3200
FDB		FDB GE	1500	120	R7-S	400	3200


SUPPLIED WITH:

- Color frame
- Safety mesh
- 2 m. Power supply cable
- R-7s lampholders

ACCESSORIES

Iris CYC

40-431	31-01	45-42	00-54				



IRIS CYC 53-21

L	230mm. (9.6")
W	950mm. (25.61")
H	420mm. (16.54")
	7.8kg. (17.19 Lbs.)
	560x400x500mm. (22.06"x15.76"x19.7")

- These equipments comply with all applicable European directives and safety standards

