

FRESNELS LED



6500K°



2700K°

SPL-200/BI/CPT

FRESNEL LED COMPACT 200W VARIABLE WHITE 2700K° TO 6500K°

- High efficient led 200w Bi-colour CRI ≥ 95
- Power consumption: 100w each colour
- Power requirements: 90V-240V 50/60Hz
- Control method: DMX or local (manual) dimming
- Adjustable Colour temperature: 2700K° to 6500K°
- Flicker free
- Fresnel lens Ø 120mm
- Powercom for power daisy chain
- MO manual operation version - PO pole operation version

ACCESSORIES




Barndoor 8-leaf



Colour conversion & Diffusion filter frame

DIMENSIONS




L 300mm (11.81")
W 200mm (7.87")
H 400mm (15.75")
KG 5,200 kg

PHOTOMETRIC DATA

Spot

Distance	1 mts	2 mts	3 mts	4 mts
Center beam	15047 lux	4335 lux	2326 lux	1385 lux
Light beam Ø	0,30 mts	0,50 mts	0,75 mts	1,00 mts
CCT K°	2800	2800	2800	2800
CRI	95	95	95	95

Center beam	22200 lux	6994 lux	3336 lux	2005 lux
CCT K°	6500	6500	6500	6500
CRI	95	95	95	95



Flood

Distance	1 mts	2 mts	3 mts	4 mts
Center beam	2778 lux	680 lux	308 lux	190 lux
Light beam Ø	1,4 mts	2,7 mts	4,1 mts	5,5 mts
CCT K°	2800	2800	2800	2800
CRI	95	95	95	95

Center beam	3965 lux	990 lux	460 lux	285 lux
CCT K°	6500	6500	6500	6500
CRI	95	95	95	95

KIT CONTENTS

Lamphead
Barndoor 4-leaf
Filter frame
Safety grid
2 m power supply cable