

FRESNEL LED 450W RGBW

FRESNELS LED

Fresnels LED 450W RGBW, built with aluminum profiles and steel, on modern and compact design, ensuring maximum dissipation and lightweight. High power RGBW Leds 450W allow to create several colors and effects for large areas.
Efficient optical system uses high quality reflector and glass fresnel lens 250mm diameter to ensure maximum lighting performance.
The FRESNEL LED can be controlled via DMX from the console or manually from the control panel on the same fresnel Led. The control panel has an LCD and buttons to set the display DMX address, as well as programming manual control. They are equipped with high quality drivers. Flicker free, and noiseless turbine, to ensure maximum extension of the lifetime of the LED.
Available models Manual and Pole Operated

MODELOS

SPL-450 RGBW

- Power tool to create full colour palette and effects.
- Ideal for lighting large areas.
- High power led 450W RGBW.
- Focus control for getting narrow and wide beam.
- Control panel DMX and Manual to select effects.
- Power consumption: 450W.
- Power requirements: 110V-240V 50/60Hz.
- Fresnel lens Ø 175mm.

FRESNEL LED 400w RGBW SPL-400RGBW

SPOT						
Distance	3 mts	4 mts	5 mts	6 mts	7 mts	8 mts
Center beam						
WHITE	1465 lux	990 lux	785 lux	607 lux	489 lux	395 lux
RED	500 lux	445 lux	337 lux	270 lux	180 lux	150 lux
BLUE	175 lux	124 lux	105 lux	83 lux	66 lux	47 lux
GREEN	1163 lux	898 lux	738 lux	561 lux	436 lux	328 lux
Light beam Ø	1,20 mts	1,60 mts	2,00 mts	2,30 mts	2,70 mts	3,10 lux



FLOOD						
Distance	3 mts	4 mts	5 mts	6 mts	7 mts	8 mts
Center beam						
WHITE	875 lux	556 lux	345 lux	248 lux	198 lux	170 lux
RED	252 lux	164 lux	110 lux	82 lux	65 lux	54 lux
BLUE	104 lux	69 lux	55 lux	32 lux	26 lux	20 lux
GREEN	602 lux	330 lux	235 lux	176 lux	136 lux	97 lux
Light beam Ø	3,00 mts	3,40 mts	3,70 mts	4,30 mts	5,50 mts	7,00 lux

FICHA TÉCNICA

www.dexel.com







FORNECIDO COM:

- Barndoor 4-leaf.
- Filter frame.
- Safety grid.
- 2 m power supply cable